



The Sullair 200H Portable Air Compressor

200 cfm at 150 psig ■ 5.7 m³/min at 10 bar

- Rotary screw compressor
- Removable modular canopy
- Adjustable height hitch
- Wheel bearing grease fittings
- Large tool box compartment
- Curbside instrument panel
- Protective shutdown switches

- SSAM – Shutdown System and Annunciation Module
- Idle warm-up valve
- Rocker type start switch
- Fuel/Water separator
- Two-stage air filters
- 0 to 100% capacity control

- Pneumatic inlet valve
- AWF Compressor Fluid
- Galvanneal sheet metal
- Durable powder coat finish
- Wide track
- Recessed tail lights
- Rear bumper


SULLAIR
Always air. Always there.™



Curbside Instrument Panel Featuring SSAM
Shutdown System & Annunciation Module.



Wheel Bearing Grease Fitting
Offers convenient wheel bearing lubrication thru zerk fittings.



Rotary Screw Design
by Sullair, the pioneer in rotary screw technology.



Sullair AWF Compressor Fluid
Improved hot and cold weather lubrication. Longer compressor fluid life. Extended air end warranty.

Designed for Total Accessibility and Reliability

Rotary Screw Compressor

Ample Service Doors

- Large service doors provide access to fuel tank, engine, compressor and tool compartment
- Service doors feature non-rusting hinges, with built-in weather strip and stainless steel T-type door retainers
- Rear service panel provides access to side by side compressor fluid cooler and engine radiator
- Serviceable components within easy reach
- Routine maintenance is simplified
- Reduced downtime and service cost

Modular Canopy and Frame

- Canopy easily removed in one piece for major service
- Modular design reduces replacement costs
- Exposed, single point lifting bail

0 to 100% Capacity Control

- Pneumatic inlet valve and unloaded starting

Highway Towable Running Gear

- 3" square drawbar
- Adjustable height hitch (14", 16", 18")
- Quick-change hitch
- Screw jack with pad
- Transport security chains
- Heavy duty leaf spring suspension
- Wide track stability

Large Curbside Tool Box

Curbside Instrument Panel

- Hinged, padlockable cover
- Mechanical air pressure gauge and hourmeter
- Rocker type engine start switch
- Idle warm-up switch

High/Low Pressure Selector Switch

- Allows dual pressure capability without making mechanical adjustments

SSAM—Shutdown System & Annunciation Module

- Shutdown with annunciator light for high compressor temperature, high engine coolant temperature, low engine oil pressure and engine under-speed

Durable, Baked-on Powder Coat Finish

Two-Stage Dry Type Air Filters

- Separate filters for engine and compressor

Tier 4 Interim / Stage III B Emissions Compliant Engine

Air End Warranty

- 2-year standard warranty
- 5-year or 10,000-hour warranty when continuously serviced at the recommended intervals with Sullair AWF Compressor Fluid and filters

Quiet Operation

- Meets US EPA sound requirements of 76 dBA @ 7 meters

Customize the compressor to meet your specific requirements with Sullair's options

Special paint
Hose reels, single and dual
Spark arrestor
Fuel level gauge
Gauge package

Tachometer
Brakes (recommended where required by law)
Mechanical parking brakes
Block heater

Ball hitch
Air filter maintenance indicators
Air filter safety elements
Low fuel shutdown

SPECIFICATIONS, WEIGHTS AND DIMENSIONS—SULLAIR 200H PORTABLE COMPRESSOR

Delivery @ Rated Pressure	Rated Pressure		Pressure Range		Designated Model	Weight (wet)		Weight		Length (dry)		Length (drawbar)		Width (canopy)		Height		Track Width		Tire Size (load range)
	psig	bar	psig	bar		lbs	kg	lbs	kg	in	mm	in	mm	in	mm	in	mm	in	mm	
200 acfm 94.4 l/s 5.7 m³/min	150	10	80-150	5.5-10	2-Wheel	2640	1196	2395	1085	143.3	3640	85.1	2162	65.4	1661	59.9	1522	55	1397	205/75D15
					Less Running Gear	2385	1081	2140	969	-	-	85.1	2162	47.5	1207	49.0	1245	-	-	-
Engine Make	Engine Type	Engine Model	Displacement		Cylinders	Bore and Stroke		Rated Speed	Rated Power											
Caterpillar	Diesel	C3.4 (Tier 4 Interim)	201	3272	4	3.70 x 4.72	94 x 120	2500	74	56										

Capacity per CAGI/PNEUROP PN2CPTC3. (Annex D to ISO 1217)



Sullair
3700 East Michigan Boulevard
Michigan City, IN 46360
Telephone: 219-879-5451
www.sullair.com

© Copyright 2014 Sullair. All rights reserved.
The color green is a registered trademark of Sullair.
Specifications subject to change without notice.
SSL-1215EN 1404R

