

COMPRESSOR DATA SHEET Rotary Screw Compressor

| MODEL DATA - FOR COMPRESSED AIR | | | | | |
|---------------------------------|--|----------------|-------------------------|--|--|
| 1 | Manufacturer: Atlas Copco Compressors, Inc. | | | | |
| 2 | Model Number: GA55C-150W | | | | |
| | ☐Air-cooled ✓Water-cooled | # of Stages: 1 | | | |
| | ✓Oil-injected □Oil-free | VALUE | UNIT | | |
| 3 | Rated Capacity at Full Load Operating Pressure a, e | 273 | acfm ^{a, e} | | |
| 4 | Full Load Operating Pressure ^b | 150 | psig ^b | | |
| 5 | Maximum Full Flow Operating Pressure ^c | 157 | psig ^c | | |
| 6 | Drive Motor Nameplate Rating | 75 | hp | | |
| 7 | Drive Motor Nameplate Nominal Efficiency | 94.0 | percent | | |
| 8 | Fan Motor Nameplate Rating (if applicable) | NA | hp | | |
| 9 | Fan Motor Nameplate Nominal Efficiency | NA | percent | | |
| 10 | Total Package Input Power at Rated Capacity and Full Load Operating Pressure ^d | 65.4 | kW^d | | |
| 11 | Specific Package Input Power at Rated Capacity and Full Load Operating Pressure ^e | 23.95 | kW/100 cfm ^e | | |

NOTES:

- a. Measured at the discharge terminal point of the compressor package in accordance with the CAGI/PNEUROP PN2CPTC2 Test Code (Annex C to ISO 1217). ACFM is actual cubic feet per minute at inlet conditions.
- b. The operating pressure at which the Capacity (Item 3) and Electrical Consumption (Item 10) were measured for this data sheet.
- c. Maximum pressure attainable at full flow, usually the unload pressure setting for load/no load control or the maximum pressure attainable before capacity control begins. May require additional power.
- d. Total package input power at other than reported operating points will vary with control strategy.
- e. Tolerance is specified in the CAGI/PNEUROP PN2CPTC2 Test Code (Annex C to ISO 1217) as follows:

| | Flow Rate d conditions | Volume Flow Rate | Specific Energy Consumption |
|----------------------------|-----------------------------|------------------|-----------------------------|
| <u>m³ / min</u> | <u>ft³ / min</u> | % | % |
| Below 0.5 | Below 15 | +/- 7 | +/- 8 |
| 0.5 to 1.5 | 15 to 50 | +/- 6 | +/- 7 |
| 1.5 to 15 | 50 to 500 | +/- 5 | +/- 6 |
| Above 15 | Above 500 | +/- 4 | +/- 5 |

Member



This form was developed by the Compressed Air and Gas Institute for the use of its members. CAGI has not independently verified the reported data.