

## **COMPRESSOR DATA SHEET Rotary Screw Compressor**

MODEL DATA – FOR COMPRESSED AIR			
1	Manufacturer: Ingersoll-Rand		
2	Model Number: <b>HXPE500-2S</b> X Air-cooled Water-cooled  X Oil-injected Oil-free	# of Stages:	2 UNIT
3	Rated Capacity at Full Load Operating Pressure <sup>a</sup>	1879	acfm <sup>a</sup>
4	Full Load Operating Pressure b	200	psig <sup>b</sup>
5	Maximum Full Flow Operating Pressure <sup>c</sup>	210	psig <sup>c</sup>
6	Drive Motor Nameplate Rating	500	hp
7	Drive Motor Nameplate Nominal Efficiency	95.1	percent
8	Fan Motor Nameplate Rating (if applicable)	20	hp
9	Fan Motor Nameplate Nominal Efficiency	86.5	percent
10	Total Package Input Power at Rated Capacity and Full Load Operating Pressure <sup>d</sup>	450.9	kW <sup>d</sup>
11	Specific Package Input Power at Rated Capacity and Full Load Operating Pressure	24.0	kW/100 cfm

## NOTES:

- Measured at the discharge terminal point of the compressor package in accordance with the CAGI/PNEUROP PN2CPTC2 Test Code (Annex C to ISO 1217). ACFM is actual cubic feet per minute at inlet conditions.
- b. The operating pressure at which the Capacity (Item 3) and Electrical Consumption (Item 10) were measured for this data sheet.
- c. Maximum pressure attainable at full flow, usually the unload pressure setting for load/no load control or the maximum pressure attainable before capacity control begins. May require additional power.
- d. Total package input power at other than reported operating points will vary with control strategy.

## Member



This form was developed by the Compressed Air and Gas Institute for the use of its members. CAGI has not independently verified the reported data.