

## **COMPRESSOR DATA SHEET**

## **Rotary Screw Compressor**

MODEL DATA - FOR COMPRESSED AIR			
1	Manufacturer: Kaeser Compressors, Inc.		
	Model Number: SFC 22 - 110 psig		
2	X Air-cooled Water-cooled	# of Stages:	1
	X Oil-injected Oil-free	VALUE	UNIT
3	Rated Capacity at Full Load Operating Pressure <sup>a</sup>	158	acfm <sup>a</sup>
4	Full Load Operating Pressure <sup>b</sup>	100	psig <sup>b</sup>
5	Maximum Full Flow Operating Pressure <sup>c</sup>	110	psig <sup>c</sup>
6	Drive Motor Nameplate Rating	30	hp
7	Drive Motor Nameplate Efficiency	91.7	percent
8	Fan Motor Nameplate Rating (if applicable)	0.75	hp
9	Fan Motor Nameplate Efficiency	67	percent
10	Total Package Power Input at Rated Capacity and Full Load Operating Pressure <sup>d</sup>	29.7	$\mathbf{kW}^{\mathrm{d}}$
11	Specific Package Input Power at Rated Capacity and Full Load Operating Pressure	18.8	kW/100 cfm

## NOTES:

- Measured at the discharge terminal point of the compressor package in accordance with the CAGI/PNEUROP PN2CPTC2 Test Code (Annex C to ISO 1217); acfm is actual cubic feet per minute at inlet conditions.
- The operating pressure at which the Capacity (item 3) and Electrical Consumption (item 10) were measured for
- Maximum pressure attainable at full flow, usually the unload pressure setting for load/no load control or the maximum pressure attainable before capacity control begins. May require additional power.
- Total package input power at other than reported operating points will vary with control strategy.

## Member:



This form was developed by the Compressed Air and Gas Institute for the use of its members. CAGI has not independently verified the reported data.

Form Number ROT 030