COMPRESSOR DATA SHEET

Rotary Screw Variable Frequency Drive Compressor

MODEL DATA - FOR COMPRESSED AIR		
Manufacturer: Sullair Corp		
Model Number: 7507V		Date: January 1, 2009
X Air-cooled Water-cooled		
X Oil-injected Oil-free	# of Stages:	1
Full Load Operating Pressure	100	psig ^b
Maximum Full Flow Operating Pressure	100	psig ^c
Drive Motor Nameplate Rating	100	hp
Drive Motor Nameplate Efficiency	95.4	percent
Fan Motor Nameplate Rating (if applicable)	3	hp
Fan Motor Nameplate Efficiency	87.5	percent
Input Power (kW)	Capacity (acfm) ^{a,e}	Specific Power (kW/100 acfm) ^e
93.7	493.0	19.01
80.5	419.1	19.22
67.4	345.1	19.52
54.2	271.2	19.98
41.0	197.2	20.79
27.8	123.3	22.57
Total Package Input Power at Zero Flow ^d	0.0	kW
40.00 40.00 A 30.00 A 30.00 10.00 10.00 Cape	300.0 400.0 acity (ACFM)	500.0
	MODEL DATA - FOR CO Manufacturer: Sullair Corp Model Number: 7507V X Air-cooled Water-cooled X Oil-injected Oil-free Full Load Operating Pressure Maximum Full Flow Operating Pressure Drive Motor Nameplate Rating Drive Motor Nameplate Efficiency Fan Motor Nameplate Efficiency Input Power (kW) 93.7 80.5 67.4 54.2 41.0 27.8 Total Package Input Power at Zero Flow ^d	Model Number: 7507V X Air-cooled Water-cooled X Oil-injected Oil-free # of Stages: Full Load Operating Pressure 100 Maximum Full Flow Operating Pressure 100 Drive Motor Nameplate Rating 100 Drive Motor Nameplate Efficiency 95.4 Fan Motor Nameplate Efficiency 87.5 Input Power (kW) Capacity (acfm) ^{a,c} 93.7 493.0 80.5 419.1 67.4 345.1 54.2 271.2 41.0 197.2 27.8 123.3 Total Package Input Power at Zero Flow ^d 0.0

Member:

- a. Measured at the discharge terminal point of the compressor package in accordance with
 - Annex E to ISO 1217; acfm is actual cubic feet per minute at inlet conditions.
- b. The operating pressure at which the Capacity and Electrical Consumption were measured for this data sheet.
- c. Maximum pressure attainable at full flow, usually the unload pressure setting for load/no load control or the maximum pressure attainable before capacity control begins. May require additional power.
- d. No Load Power. In accordance with ISO 1217, Annex E, if measurement of no load power equals less than 1%, manufacturer may state "not significant" or "0" on the test report.
- e. Tolerance is specified in Annex E to ISO 1217 as follows:

 NOTE: The terms "power" and "energy" are synonymous for purposes of this document





