COMPRESSOR DATA SHEET

Rotary Screw Variable Frequency Drive Compressor

MODEL DATA - FOR COMPRESSED AIR						
1	Manufacturer: Sullair Corp					
	Model Number: 7510PV		Date: March 1, 2009			
2	X Air-cooled Water-cooled					
	X Oil-injected Oil-free	# of Stages:	1			
3	Full Load Operating Pressure	150	psig ^b			
4	Maximum Full Flow Operating Pressure	150	psig ^c			
5	Drive Motor Nameplate Rating	100	hp			
6	Drive Motor Nameplate Efficiency	rive Motor Nameplate Efficiency 95.4 percent				
7	Fan Motor Nameplate Rating (if applicable)	3	hp			
8	Fan Motor Nameplate Efficiency	87.5	percent			
	Input Power (kW)	Capacity (acfm) ^{a,e}	Specific Power (kW/100 acfm) ^e			
	91.3	420.0	21.74			
	78.4	357.0	21.97			
9	65.6	294.0	22.33			
	52.8	231.0	22.84			
	40.0	168.0	23.80			
	26.4	105.0	25.13			
	16.6	63.0	26.38			
10	Total Package Input Power at Zero Flow ^d	0.0	kW			
11		250.0 300.0 350.0 pacity (ACFM)	400.0 450.0			

Member:

- a. Measured at the discharge terminal point of the compressor package in accordance with Annex E to ISO 1217; acfm is actual cubic feet per minute at inlet conditions.
- b. The operating pressure at which the Capacity and Electrical Consumption were measured for this data sheet. c. Maximum pressure attainable at full flow, usually the unload pressure setting for load/no load control or the maximum pressure attainable before capacity control begins. May require additional power.
- d. No Load Power. In accordance with ISO 1217, Annex E, if measurement of no load power equals less than 1%,
- manufacturer may state "not significant" or "0" on the test report.

 e. Tolerance is specified in Annex E to ISO 1217 as follows:

 NOTE: The terms "power" and "energy" are synonymous for purposes of this document



Volume	e Flow Rate		Specific
at specifi	ed conditions	Volume Flow Rate	Energy
$\underline{\mathbf{m}^3 / \min}$	ft ³ / min	%	%
Below 0.5	Below 15	+/- 7	+/- 8
0.5 to 1.5	15 to 50	+/- 6	+/- 7
1.5 to 15	50 to 500	+/- 5	+/- 6
Above 15	Above 500	+/- 4	+/- 5