COMPRESSOR DATA SHEET Rotary Screw Compressor

MODEL DATA - FOR COMPRESSED AIR					
1	Manufacturer: Sullair Corp				
	Model Number: 3009P				
2	X Air-cooled Water-cooled	# of Stages:	1		
	X Oil-injected Oil-free	VALUE	UNIT		
3	Rated Capacity at Full Load Operating Pressure a, f	182	acfm ^{a,f}		
4	Full Load Operating Pressure ^b	125	psig		
5	Maximum Full Flow Operating Pressure ^c	125	psig ^c		
6	Drive Motor Nameplate Rating	40	hp		
7	Drive Motor Nameplate Nominal Efficiency	93.0	percent		
8	Fan Motor Nameplate Rating (if applicable)	1.5	hp		
9	Fan Motor Nameplate Nominal Efficiency	84.0	percent		
10	Total Package Input Power at Zero Flow ^e	9.3	kW ^e		
11	Total Package Input Power at Rated Capacity and Full Load Operating Pressure	37.2	kW ^d		
12	Specific Package Input Power at Rated Capacity and Full Load Operating Pressure ^g	20.44	kW/100 cfm ^g		

NOTES:

- a. Measured at the discharge terminal point of the compressor package in accordance with the CAGI/PNEUROP PN2CPTC2 Test Code (Annex C to ISO 1217). ACFM is actual cubic feet per minute at inlet conditions.
- b. The operating pressure at which the Capacity (Item 3) and Electrical Consumption (Item 10) were measured for this data sheet.
- c. Maximum pressure attainable at full flow, usually the unload pressure setting for load/no load control or the maximum pressure attainable before capacity control begins. May require additional power.
- d. Total package input power at other than reported operating points will vary with control strategy.
- e. Tolerance is specified in the CAGI/PNEUROP PN2CPTC2 Test Code (Annex C to ISO 1217)
- f, g. Tolerance is specified in the CAGI/PNEUROP PN2CPTC2 Test Code (Annex C to ISO 1217) as follows:

	at specified conditions		
Member	$\underline{m}^{3} / \underline{min}$	<u>ft³ / min</u>	
MPRESSED	Below 0.5	Below 15	
CACI	0.5 to 1.5	15 to 50	
ÇAGI	1.5 to 15	50 to 500	
Bee mortific	Above 15	Above 500	
TO INSIVE			

	Flow Rate d conditions	Volume Flow Rate f	Specific Energy Consumption ^g
$\underline{\mathbf{m}}^{3} / \underline{\mathbf{min}}$	<u>ft³ / min</u>	%	%
Below 0.5	Below 15	+/- 7	+/- 8
0.5 to 1.5	15 to 50	+/- 6	+/- 7
1.5 to 15	50 to 500	+/- 5	+/- 6
Above 15	Above 500	+/- 4	+/- 5

This form was developed by the Compressed Air and Gas Institute for the use of its members. CAGI has not independently verified the reported data.